



 MALE TANK FITTING						
Product Code	T1 BSPF	a mm	b mm	c mm	d mm	e mm
STF15	½" (15mm)	38.6	13.9	5.5	55.0	31.0
STF20	¾" (20mm)	45.1	21.5	6.2	55.0	35.0
STF25	1" (25mm)	54.1	27.7	6.5	55.0	38.0
STF32	1¼" (32mm)	64.1	33.6	7.2	55.0	43.0
STF40	1½" (40mm)	72.0	40.6	8.2	55.0	51.0
STF50	2" (50mm)	84.6	52.6	8.2	55.0	55.0



FOR REFERENCE USE ONLY.
 WITH OUR POLICY OF CONTINUING PRODUCT DESIGN AND DEVELOPMENT, SPECIFICATIONS, CODE NUMBERS AND ITEMS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

© COPYRIGHT: HANSEN PRODUCTS (NZ) LIMITED.

The above stated dimensions apply to both the Black and the White Male Tank Fitting

RECOMMENDED HOLE SAW SIZES

- STF 15mm = 22mm or 7/8" Hole Saw
- STF 20mm = 27mm or 1 1/16" Hole Saw
- STF 25mm = 34mm or 1 3/8" Hole Saw
- STF 32mm = 42mm or 1 5/8" Hole Saw
- STF 40mm = 48mm or 1 7/8" Hole Saw
- STF 50mm = 60mm or 2 3/8" Hole Saw

MINIMUM RECOMMENDED HOLE SIZES

- Hole Size for STF 15mm = 22mm
- Hole Size for STF 20mm = 27mm
- Hole Size for STF 25mm = 34mm
- Hole Size for STF 32mm = 42mm
- Hole Size for STF 40mm = 48mm
- Hole Size for STF 50mm = 60mm